

TECHNICAL DATA SHEET

SX INSTANT PLASTER FILLER

A non-shrinking, ultra-light, ready mixed filler for filling and repairing cracks and holes in walls and ceilings. It is quick drying and can be over-painted with emulsion based paint 10-20 minutes after application, subject to ambient conditions. After curing the product can be sanded.

USES - For filling joints and screw holes in plasterboard walls and ceilings. For filling and repairing holes and in static joints in concrete, brickwork and plaster.

COLOURS: White

PACKAGING: 310ml cartridge (packed 1 x 25)

DIRECTIONS - Surfaces must be clean, dry and free from dust, grease and other loose material. Cut the cartridge seal and screw on the nozzle which should be cut to your required size. Using a skeleton gun, apply the filler into the gap or joint ensuring a good solid fill. Smooth off using a putty knife. Finish with a wet taping knife or wet trowel.

HEALTH & SAFETY – This product contains a preservative against microbial deterioration. Contains: a mixture of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2-isothiazol-3-one [EC no. 220-239-6] (3:1). 1,2-benzisothiazol-3(2H)-one (CAS: 2634-33-5). May produce an allergic reaction. Safety data sheet available on request. Keep out of the reach of children. Do not take internally. Use only in well ventilated areas. If after inhalation one feels unwell then supply fresh air. After any skin contact wash off immediately. After eye contact wash open eye for several minutes under running water. If any symptoms persist consult a doctor and take a cartridge with you. Dispose of empty packaging responsibly.

LIMITATIONS - Among others not recommended for use on PE, PP, PC, PMMA, PTFE, neoprene and bituminous surfaces. Not suitable for construction joints, outside applications and continuous submersion in water. Painting over with highly filled emulsion paint can cause craze cracking on the paint surface. Due to the variety of paint compositions, we do recommend preliminary tests for compatibility. Curing time will vary dependent on temperature and humidity of environment. Adhesion tests prior to application are recommended. It is the user's responsibility to determine suitability. Store between +5°C and +25°C in cool, dry conditions.

LIABILITY The information given is the result of our tests and experience and is believed to be accurate and reliable. However, as Siroflex Limited cannot know all the uses that its products may be put to and as application methods are out of our control, it is the user's responsibility to determine suitability of use.

TECHNICAL DATA	DIMENSION	SX INSTANT PLASTER FILLER
Basis		Emulsion
Application temperature	°C	+5 - +30
Consistency		Paste
Paintable after - 23°C/55%RF	min	10-20
Cure time (2mm) - 23°C/55%RF	hour	1 – 8
Density	g/ml	0.57
Shrinkage - 23°C/55%RF	%	Slight
Frost resistant up to –15°C during transport		Yes
Shelf life between +5°C and +25°C	month	12

QUANTITY ESTIMATOR - Width x depth of joint x length (in linear metres) of joint, divided by the volume of tube in ml = number of cartridges required.

Click [here](#) for full Health & Safety information.

