

HIGH PERFORMANCE WHITE LITHIUM GREASE



PRODUCT OVERVIEW

WD-40® Specialist® High Performance White Lithium Grease is a thicker solution which provides long term lubrication that won't drip nor run. It's great for metal to metal applications, reducing friction to ensure your tools and equipment keep moving smoothly. This product can be used on load bearing metal connections.

FEATURES AND BENEFITS

- ⊕ For use on metal to metal connections
- ⊕ Water and heat resistant lubricant
- ⊕ Long last protection against rust and corrosion
- ⊕ Ideal for load bearing application
- ⊕ High viscosity lubricant
- ⊕ Withstands temperatures of -18°C to +145°C

NSF H2 Registered #145376



NARROW SPRAY



WIDE SPRAY

TYPICAL APPLICATIONS

Motor pivot points, Bearings, Winches, Latches, Pistons, Conveyors, Overhead Door Tracks, Cables, Bearings, Runners, Water Pumps, Gear & Brake Mechanisms, Metal parts, Hinges, Catches.

DIRECTIONS FOR USE

Shake can well. Apply by spraying directly on surface to be lubricated and protected.

TECHNICAL DATA

| PROPERTY | HIGH PERFORMANCE WHITE LITHIUM GREASE |
|--|--|
| Odour | Pleasant lemon odour |
| SG | 0.84 - 0.86 |
| Temperature range | Effective performance at temperatures from -18°C to +145°C |
| Solubility | Not miscible with water |
| NSF category | H2 |
| Flammability | Classed as extremely flammable under current legislation |
| Compatibility | Ideal for metal-to-metal application |
| Lubrication ASTM D-4172 | Scar depth 0.41 mm |
| Extreme pressure lubrication ASTM 3233 | 1151 lb |
| Corrosion protection ASTM B-117 | 0 at 72h |

PACKAGING SPECIFICATIONS

| PRODUCT NUMBER | UNIT SIZE | CASE SIZE |
|----------------|-----------|------------|
| 44390 | 400ml | 400ml x 12 |

