

Date: 19.11.2014 Ref: 0036.13.DB/DL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Trade name: SX CONTRACTORS SANITARY SILICONE

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Sealant

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SIROFLEX LIMITED

Dodworth Business Park

Dodworth

Barnsley

South Yorkshire

S75 3SP

Tel: 01226 771600 Fax: 01226 771601

· Further information obtainable from:

www.siroflex.co.uk info@siroflex.co.uk

1.4 Emergency telephone number:

Tel: 01226 771600 (Office Hours Only)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is not classified according to the CLP regulation.

- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC Not applicable.
- · Information concerning particular hazards for human and environment:

The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- Additional information:

Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.

Safety data sheet available on request.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

– GI



Date: 19.11.2014 Ref: 0036.13.DB/DL

Trade name: SX CONTRACTORS SANITARY SILICONE

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

- 3.2 Chemical characterization: Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 64742-46-7	Distillates (petroleum), hydtrotreated middle	10-<30%
EC number: 934-956-3	X Xn R65	
	♦ Asp. Tox. 1, H304	
CAS: 64742-47-8	Distillates (petroleum), hydrotreated light	5-<10%
EINECS: 265-149-8	X Xn R65	
Reg.nr.: 01-21198227000-58	R66-67	
	♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336	
CAS: 64359-81-5	4,5-dichloro-2-octyl-2H-isothiazol-3-one	<1.0%
EINECS: 264-843-8	😡 T R23; 🔄 C R34; 🗙 Xn R22; 🗙 Xi R43; 🝢 N R50	
	Acute Tox. 2, H330; Skin Corr. 1C, H314; Aquatic Acute 1, H400; Acute Tox. 4, H302; Skin Sens. 1, H317	

• Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eve contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- -5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Pick up mechanically.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 3)



Date: 19.11.2014 Replaces: 27.05.2014 Ref: 0036.13.DB/DL

Trade name: SX CONTRACTORS SANITARY SILICONE

(Contd. of page 2)

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Use only in well ventilated areas.
- Information about fire and explosion protection: No special measures required.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- **Information about storage in one common storage facility:** Not required.
- · Further information about storage conditions: None.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

- Respiratory protection: Not required.
- **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- Appearance:

Form: Pasty

Colour: Various colours
Odour: Like ethanoic acid

(Contd. on page 4)



Date: 19.11.2014 Replaces: 27.05.2014 Ref: 0036.13.DB/DL

Trade name: SX CONTRACTORS SANITARY SILICONE

		(Contd. of page 3
Odour threshold:	Not determined.	
· pH-value:	Undetermined.	
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. Undetermined.	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	Undetermined.	
Decomposition temperature:	Not determined.	
· Self-igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits: Lower: Upper:	Undetermined. Undetermined.	
· Vapour pressure:	Undetermined.	
Density at 20 °C: Relative density Vapour density Evaporation rate	0.97 g/cm ³ Not determined. Not determined. Not determined.	
Solubility in / Miscibility with water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wa	ter): Not determined.	
Viscosity: Dynamic: Kinematic:	Not determined. Not determined.	
Solvent content: VOC (EC) 9.2 Other information	0.00 % No further relevant information available.	

SECTION 10: Stability and reactivity

- 10.1 Reactivity
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

GB



Date: 19.11.2014 Ref: 0036.13.DB/DL

Trade name: SX CONTRACTORS SANITARY SILICONE

(Contd. of page 4)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

T TO /T		1 46	1 '0" /*
	(SII VOINE	relevant tor	classification:

64742-46-7 Distillates (petroleum), hydtrotreated middle

Oral LD50 >2000 mg/kg (rat)
Dermal LD50 >2000 mg/kg (rabbit)

- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Disposal must be made according to official regulations.
- · European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- · 14.1 UN-Number
- · ADR, ADN, IMDG, IATA

Void

(Contd. on page 6)



Date: 19.11.2014 Ref: 0036.13.DB/DL

Trade name: SX CONTRACTORS SANITARY SILICONE

		(Contd. of page 5)
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards: · Marine pollutant:	No	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Transport in bulk according to Ann MARPOL73/78 and the IBC Code	ex II of Not applicable.	
· UN "Model Regulation":	-	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Labelling of 'treated articles' according to Regulation (EU) 528/2012, Article 58 This product contains a biocidal product for the preservation of the dry film. Contains: 4,5 dichloro-2-octyl-2H-isothiazol-3-one (CAS: 64359-81-5)
- · National regulations:
- · Other regulations, limitations and prohibitive regulations -
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H330 Fatal if inhaled.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- R22 Harmful if swallowed.
- R23 Toxic by inhalation.
- R34 Causes burns.
- R43 May cause sensitisation by skin contact.
- R50 Very toxic to aquatic organisms.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.
- · Department issuing MSDS: Product safety department.
- · Contact: Pascal Timmermans / Kees van Bemmel

(Contd. on page 7)



Date: 19.11.2014 Ref: 0036.13.DB/DL

Trade name: SX CONTRACTORS SANITARY SILICONE

(Contd. of page 6)

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Acute Tox. 4: Acute toxicity, Hazard Category 4 Acute Tox. 2: Acute toxicity, Hazard Category 2

Skin Corr. 1C: Skin corrosion/irritation, Hazard Category 1C Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

-GB