

Boiled Linseed Oil

Double Boiled Linseed Oil

Product Information Sheet

Description

Bartoline Boiled Linseed Oil is suitable for replacing the natural sheen that wood can lose after long periods drying in the sun. This is a popular wood treatment to replace natural oils removed by weathering. Bartoline Boiled Linseed Oil can be used internally or externally on unpolished wood surfaces. It contains special additives, which hastens the drying process. Hardwoods such as Oak and Teak should be treated with Bartoline Teak Oil.

Preparation

Ensure that the surface to be treated is thoroughly clean and dry. Apply Boiled Linseed Oil by either brushing or using a cloth. For best results apply multiple thin coats allowing each coat to dry before recoating. Remove any excess Linseed oil with a dry clean cloth. Drying time is approximately 16 hours however this will vary depending upon thickness of coating applied and local climatic conditions.

Health & Safety

See MSDS for full information.

Not classified as hazardous.

Caution – Do not leave soiled application cloths where they may constitute a fire hazard, as they may be liable to spontaneous combustion. Ideally soiled cloths should be immediately burnt; if this is not possible they should be washed in soapy water and hung outside to dry.

Technical Data

Physical State:	Liquid
Form/colour:	Dark reddish brown
Odour:	Oily type
Solubility in water	Insoluble
Other Solubility	Soluble in white spirit, acetone
Flash point	Over 100 Deg C
Boiling Point	This oil, if heated, starts to decompose over 100 degrees C, and may thermally polymerise
Auto – flammability	Over 200 degrees C
Density @ 15.5 Degrees C	0.942
Viscosity @ 25 Degrees C	Approx 1 Poise
Other Data	Drying time (at 23 degrees C) 16 Hours Coverage Rate 10 Square Metres per Litre.

Packing Specification

Product / Pack Size	Quantity Per Carton	Cartons / Drums Per Pallet.
250 ml PET Bottle	12	174
500 ml PET Flask	6	144
1 Litre PET Flask	6	81
2 Litre PET Bottle	8	44
5 Litre Poly Bottle	4	40
20 Litre Drum	0	42
205 Litre Drum	0	4

Customs Tariff Code

1515 1910

Shipping Classification

Non Hazardous for shipping purposes