



<u>Patching Plaster</u> <u>Technical Data Sheet</u>

Description

Bartoline Patching Plaster is specially formulated for repairs to plaster, plasterboard, wood, brick, stone and most other building materials. Ideal for preparing surfaces before painting or wallpapering. Use Patching Plaster to fill cracks and holes in walls, ceilings and around door frames and skirting boards. The plaster gives a smooth surface perfect for wallpapering or painting. Easy to mix and simple to use. Does not shrink. Has excellent adhesion properties which keep the plaster firmly in position.

Directions

Preparation: Ensure surfaces are clean, dry and dust free. Moisten absorbent surfaces with water. Touch in nail and screw heads with an oil-based paint to prevent rusting.

Mixing: Add approximately 2.5 parts powder to 1 part cold water and mix until smooth. Always mix in a clean container. Patching plaster has a working time of approximately 1 hour so only mix an amount that can be used within this time.

Application: Apply patching plaster with a trowel in layers of no more than 12mm thick. Allow each layer to set before applying the next. Smooth over the final coating using a plastering trowel or fill proud and sand down once dry. Once the surface is completely dry it can be decorated as required.

Cleaning & Storage

All tools and mixing bowls should be cleaned with warm water before filler sets. STORE IN A DRY PLACE, KEEPING SACHET CLOSED

Health and Safety

See MSDS for full information.

Technical Data

Measurement	Value	Test Method		
Physical State	Fine Powder	Visual		
Colour	White	Visual		
Odour	Plaster of Paris type			
Flash point	Not Applicable			
VOC content	None			
рН	6.6 – 7.6	280g powder to 120g water		

Packing Specification

<u>Pack</u> <u>Size</u>	Product Code	Pack Barcode	Carton Barcode	Packs Per Carton	Cartons Per Pallet	Packs Per Pallet	<u>Ti</u>	<u>Hi</u>
1.5kg box	52710070	5010789710071	05010789829179	6	65	390	13	5

Customs Tariff Code

3214 1090

Shipping Classification

Non-Hazardous for shipping purposes