

PRODUCT DATA SHEET

EVERBUILD® Lumberjack® Wood Preserver

PENETRATES AND PRESERVES FOR LONG-LASTING PROTECTION

PRODUCT DESCRIPTION

EVERBUILD® Lumberjack® Wood Preserver is a solvent free, low odour solution based on Micro-fine active technology. The fungicides and algaecides present in this formulation are finely dispersed so that wood penetration and hence effectiveness is much greater than standard wood preservation products. In addition the use of ultra-lightfast pigments on the coloured variants give an even, fade-resistant finish which will last for years. EVERBUILD® Lumberjack® Wood Preserver is fast-drying and non-flammable; and application to wet timbers is possible without loss of performance. It is specifically designed to deeply penetrate all wood and joinery to give long-lasting protection from damage caused by wet rot, dry rot, decay and fungi.

USES

EVERBUILD® Lumberjack® Wood Preserver - Clear:

For use on interior or exterior rough-sawn or planed timber such as floorboards, joists, roof timbers, window frames and doors. This product is an ideal pre-treatment which may be overpainted, varnished, or stained when dry (allow 48 hours drying time). For interior applications it may also be left as the final finish for a natural wood effect; however, when used externally, overpainting/staining is required, as this product does not repel water.

NOTE: product is milky out of the can but dries clear.

EVERBUILD® Lumberjack® Wood Preserver - Fir

Green, Dark Oak, Golden Chestnut & Red Cedar: Ideal for general use on rough-sawn or planed timber such as window frames, fences, sheds, cladding, horticultural timber, roof timber, joists etc. Fir Green is particularly useful for easy identification of treated timbers and horticultural work. These colours should be over-painted, stained or varnished later if required.

CHARACTERISTICS / ADVANTAGES

- Solvent-free formula.
- Non-flammable.
- Internal and external use.
- Can be applied to damp timbers.

PRODUCT INFORMATION

Packaging	Clear - 1, 5, 25Ltr tins Red Cedar - 5Ltr tin Golden Chestnut - 5Ltr tin Fir Green - 1, 5, 25Ltr tins Dark Oak - 5Ltr tin
Shelf Life	Use within 2 years of manufacture.

Storage Conditions

Store at moderate (5°C to 30°C) temperatures in original containers away from children.

Consumption / Yield / Dosage (PRINT single line)

Use only as supplied (do not dilute). 1 litre will treat 3 – 4 square metres.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

Shake well before use. Apply by brush, spray or dipping. Apply a minimum of two coats if brushing or spraying. The second coat should be applied after the first coat has soaked in but before it is dry. Pay particular attention to thoroughly soaking the end grain. Where possible, and for maximum protection, dip the end grains of the timber for a minimum of 3 minutes.

LIMITATIONS

- Ready to use - do not dilute.
- Always use coarse rather than fine mist generators.
- Do not apply to surfaces on which food is prepared.
- Avoid contact with bitumen, roofing felt or plastics.
- It is the user's responsibility to determine suitability for use. If in doubt, contact Technical Services Department for advice.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

See MSDS for full list of hazards.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland