



# Ready Mixed Lightweight Filler Technical Data Sheet

## **Description**

Bartoline Lightweight Filler is an easy to apply high-tech ready-to-use lightweight filler suitable for a multitude of tasks around the home and workplace. Utilising ultra-modern glass bead technology it outperforms most other conventional fillers. When filling large cracks and gaps there is no need to build layers, as no sagging or shrinkage will be evident, even on ceilings. Dries brilliant white with a perfectly smooth finish requiring NO sanding. Product may be overpainted in approximately 30 minutes. Suitable for interior or exterior use on all surfaces except plastics and metals. Not suitable for fixing structural bolts.

## **Directions**

Preparation: For best results brush out loose material and dust from crack or hole to be filled. Hairline cracks should be slightly enlarged to ensure good filler penetration. Moisten absorbent surfaces with water. Touch in nail and screw heads with an oil-based paint to prevent rusting.

Application: Do not use externally when rain is imminent. Ensure surfaces are clean, dry and dust free. Use direct from tub with a filler knife or spatula. Add a drop of water if the product appears too dry. Press firmly into cavities and smooth over surface and allow to dry. Although not normally necessary, the product may be sanded if required. When used externally protect the filled area from rain and water during setting, then seal with an oil-based paint to protect from weathering. Use only in ambient temperatures above 5°C.

## **Cleaning & Storage**

Replace lid firmly and store in a cool, dry place, not below 5°C. Clean tools with water. PROTECT FROM FROST.

## **Health and Safety**

See MSDS for full information.

#### **Technical Data**

Measurement	Value
Physical State	Paste
Colour	Brilliant White
Specific Gravity	0.20 - 0.35 g/cm³ (approx)
Flash point	Not Applicable

Bartoline Limited, Barmston Close, Beverley HU17 0LW, England. Tel: 01482 678710 | Fax: 01482 872606 | E-mail: info@bartoline.co.uk

Solids content	63% w/w
рН	8.0 – 9.0
Maximum fill	75mm in one coat – further layers may be built up.
Maximum width	50mm
Application temp	5°C to 30°C

# **Packing Specification**

Pack Size	Product Code	Pack Barcode	Carton Barcode	Packs Per Carton	<u>Cartons</u> <u>Per</u> <u>Pallet</u>	Packs Per Pallet	<u>Ti</u>	<u>Hi</u>
500ml tub	52740500	5010789740504	05010789152932	6	112	672	16	7
1L tub	52741000	5010789741006	05010789741013	6	50	300	10	5

# **Customs Tariff Code**

3214 1090

# **Shipping Classification**

Non-Hazardous for shipping purposes