

Date: 24.07.2014

Replaces: 22.05.2014

Ref: 0045.13.DBR/DL

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

#### Trade name: SX Hand Held Foam

• **1.2 Relevant identified uses of the substance or mixture and uses advised against** Filling of gaps in interior applications and cavities. For filling and isolation around window frames and doors

#### · 1.3 Details of the supplier of the safety data sheet

 Manufacturer/Supplier: Siroflex Limited
 Dodworth Busines Park, Dodworth, Barnsley, South Yorkshire, S75 3SP
 Tel: 01226 771600
 Fax: 01226 771601

#### • Further information obtainable from: info@siroflex.co.uk www.siroflex.co.uk

• **1.4 Emergency telephone number:** Tel: 01226 771600 (Office Hours Only)

### **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

# GHS08 health hazard

Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Carc. 2	H351	Suspected of causing cancer.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.

# GHS07

Harmful if inhaled.
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
May cause respiratory irritation.
May cause harm to breast-fed children.
thay eause humin to breast rea emilaten.
May cause long lasting harmful effects to aquatic life.

#### · Classification according to Directive 67/548/EEC or Directive 1999/45/EC

🗙 Xn; Harmful

R20-40-48/20: Harmful by inhalation. Limited evidence of a carcinogenic effect. Harmful: danger of serious damage to health by prolonged exposure through inhalation.



Replaces: 22.05.2014

Ref: 0045.13.DBR/DL

### Trade name: SX Hand Held Foam

	(Contd. of page 1)
Xn; So	ensitising
R42/43:	May cause sensitisation by inhalation and skin contact.
🗙 Xi; Irr	itant
R36/37/38	: Irritating to eyes, respiratory system and skin.
F+; Ez	xtremely flammable
R12:	Extremely flammable.
K12.	
R53-64:	May cause long-term adverse effects in the aquatic environment. May cause harm to breastfed babies.
The produ preparatio Warning! Classifica	on concerning particular hazards for human and environment: act has to be labelled due to the calculation procedure of the "General Classification guideline for ns of the EU" in the latest valid version. Pressurized container. tion system: fication is according to the latest editions of the EU-lists, and extended by company and literature data.
2.2 Label	
	according to Regulation (EC) No 1272/2008
The produ	ct is classified and labelled according to the CLP regulation.
Hazard p	ictograms
~	
<u></u>	1
GHS02 GI	HS07 GHS08
Signal wo	<b>rd</b> Danger
Signal wo Hazard-d	rd Danger etermining components of labelling:
Signal wo Hazard-d diphenylm	rd Danger etermining components of labelling: hethanediisocyanate, isomers and homologues
Signal wo Hazard-d diphenylm Hazard st	rd Danger etermining components of labelling: lethanediisocyanate, isomers and homologues atements
Signal wo Hazard-d diphenylm Hazard st H222-H22	rd Danger etermining components of labelling: ethanediisocyanate, isomers and homologues atements 9 Extremely flammable aerosol. Pressurised container: May burst if heated.
Signal wo Hazard-d diphenylm Hazard st H222-H22 H332	rd Danger etermining components of labelling: ethanediisocyanate, isomers and homologues atements 9 Extremely flammable aerosol. Pressurised container: May burst if heated. Harmful if inhaled.
Signal wo Hazard-d diphenylm Hazard st H222-H22 H332 H315	rd Danger etermining components of labelling: ethanediisocyanate, isomers and homologues atements 9 Extremely flammable aerosol. Pressurised container: May burst if heated. Harmful if inhaled. Causes skin irritation.
Signal wo Hazard-d diphenylm Hazard st H222-H22 H332 H315 H319	rd Danger etermining components of labelling: nethanediisocyanate, isomers and homologues atements 9 Extremely flammable aerosol. Pressurised container: May burst if heated. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation.
<b>Signal wo</b> <b>Hazard-d</b> diphenylm <b>Hazard st</b> H222-H22 H332 H315 H319 H334	rd Danger etermining components of labelling: nethanediisocyanate, isomers and homologues atements 9 Extremely flammable aerosol. Pressurised container: May burst if heated. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
<b>Signal wo</b> <b>Hazard-d</b> diphenylm <b>Hazard st</b> H222-H22 H332 H315 H319 H334 H317	rd Danger etermining components of labelling: nethanediisocyanate, isomers and homologues atements 9 Extremely flammable aerosol. Pressurised container: May burst if heated. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
<b>Signal wo</b> <b>Hazard-d</b> diphenylm <b>Hazard st</b> H222-H22 H332 H315 H319 H334 H317 H351	rd Danger etermining components of labelling: nethanediisocyanate, isomers and homologues atements 9 Extremely flammable aerosol. Pressurised container: May burst if heated. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer.
<b>Signal wo</b> <b>Hazard-d</b> diphenylm <b>Hazard st</b> H222-H22 H332 H315 H319 H334 H317 H351 H362	rd Danger etermining components of labelling: tethanediisocyanate, isomers and homologues atements 9 Extremely flammable aerosol. Pressurised container: May burst if heated. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer. May cause harm to breast-fed children.
<b>Signal wo</b> <b>Hazard-d</b> diphenylm <b>Hazard st</b> H222-H22 H332 H315 H319 H334 H317 H351 H362 H335	rd Danger etermining components of labelling: tethanediisocyanate, isomers and homologues atements 9 Extremely flammable aerosol. Pressurised container: May burst if heated. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer. May cause harm to breast-fed children. May cause respiratory irritation.
<b>Signal wo</b> <b>Hazard-d</b> diphenylm <b>Hazard st</b> H222-H22 H332 H315 H319 H334 H317 H351 H351 H362 H335 H373	rd Danger etermining components of labelling: ethanediisocyanate, isomers and homologues atements 9 Extremely flammable aerosol. Pressurised container: May burst if heated. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer. May cause harm to breast-fed children. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure.
Signal wo Hazard-d diphenylm Hazard st H222-H22 H332 H315 H319 H334 H317 H351 H362 H335 H373 H413	rd Danger etermining components of labelling: tethanediisocyanate,isomers and homologues atements 9 Extremely flammable aerosol. Pressurised container: May burst if heated. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer. May cause harm to breast-fed children. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. May cause long lasting harmful effects to aquatic life.
Signal wo Hazard-d diphenylm Hazard st H222-H22 H332 H315 H319 H334 H317 H351 H362 H335 H373 H413 Precautio	rd Danger etermining components of labelling: tethanediisocyanate,isomers and homologues atements 9 Extremely flammable aerosol. Pressurised container: May burst if heated. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer. May cause harm to breast-fed children. May cause harm to breast-fed children. May cause damage to organs through prolonged or repeated exposure. May cause long lasting harmful effects to aquatic life.
Signal wo Hazard-d diphenylm Hazard st H222-H22 H332 H315 H319 H334 H317 H351 H362 H335 H373 H413 Precautio P101	rd Danger etermining components of labelling: tethanediisocyanate, isomers and homologues atements 9 Extremely flammable aerosol. Pressurised container: May burst if heated. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer. May cause harm to breast-fed children. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. May cause long lasting harmful effects to aquatic life. mary statements If medical advice is needed, have product container or label at hand.
Signal wo Hazard-d diphenylm Hazard st H222-H22 H332 H315 H319 H334 H317 H351 H362 H335 H373 H413 Precautio P101 P102	rd Danger etermining components of labelling: tethanediisocyanate, isomers and homologues atements 9 Extremely flammable aerosol. Pressurised container: May burst if heated. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer. May cause harm to breast-fed children. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. May cause long lasting harmful effects to aquatic life. mary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children.
Signal wo Hazard-d diphenylm Hazard st H222-H22 H332 H315 H319 H334 H317 H351 H362 H335 H373 H413 Precautio P101 P102 P103	rd Danger etermining components of labelling: tethanediisocyanate, isomers and homologues atements 9 Extremely flammable aerosol. Pressurised container: May burst if heated. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer. May cause harm to breast-fed children. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. May cause long lasting harmful effects to aquatic life. mary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use.
Signal wo Hazard-d diphenylm Hazard st H222-H22 H332 H315 H319 H334 H317 H351 H362 H335 H373 H413 Precautio P101 P102	rd Danger etermining components of labelling: tethanediisocyanate, isomers and homologues atements 9 Extremely flammable aerosol. Pressurised container: May burst if heated. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer. May cause harm to breast-fed children. May cause arespiratory irritation. May cause damage to organs through prolonged or repeated exposure. May cause long lasting harmful effects to aquatic life. mary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
Signal wo Hazard-d diphenylm Hazard st H222-H22 H332 H315 H319 H334 H317 H351 H362 H335 H373 H413 Precautio P101 P102 P103	rd Danger etermining components of labelling: tethanediisocyanate, isomers and homologues atements 9 Extremely flammable aerosol. Pressurised container: May burst if heated. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer. May cause harm to breast-fed children. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. May cause long lasting harmful effects to aquatic life. mary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use.



Replaces: 22.05.2014

Ref: 0045.13.DBR/DL

#### Trade name: SX Hand Held Foam

	(Contd. of page 2)
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P263	Avoid contact during pregnancy/while nursing.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P3	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Additional inf	formation:
Contains isocy	anates. May produce an allergic reaction.
Draggyrized ag	ntainer, protect from suplicity and do not average to temperatures averaging 50°C. Do not piezo av

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.

# **SECTION 3: Composition/information on ingredients**

· 3.2 Chemical characterization: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

CAS: 9016-87-9	diphenylmethanediisocyanate, isomers and homologues	25-50%
	🗙 Xn R20; 🗙 Xn R42/43; 🗙 Xi R36/37/38	
	Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3,	
	H335	
CAS: 85535-85-9	alkanes, C14-17, chloro	5-<25%
EINECS: 287-477-0	₩ N R50/53	
	<u>R6</u> 4-66	
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Lact., H362	
CAS: 75-28-5	isobutane	2.5-10%
EINECS: 200-857-2	♦ F+ R12	
	📀 Flam. Gas 1, H220; Press. Gas, H280	
CAS: 115-10-6	dimethyl ether	2.5-10%
EINECS: 204-065-8	♦ F+ R12	
	🚸 Flam. Gas 1, H220; Press. Gas, H280	
	(Con	td. on page


**Den Braven** Date: 24.07.2014

# Safety data sheet according to 1907/2006/EC, Article 31

Replaces: 22.05.2014

Ref: 0045.13.DBR/DL

Trade name: SX Hand Held Foam



### **SECTION 4: First aid measures**

### - 4.1 Description of first aid measures - General information: Immediately remove any clothing soiled by the product. Personal protection for the First Aider. Position and transport stably in side position. In case of irregular breathing or respiratory arrest provide artificial respiration. After inhalation: Supply fresh air and to be sure call for a doctor. Take affected persons into fresh air and keep quiet. In case of unconsciousness place patient stably in side position for transportation. • After skin contact: Immediately wash with water and soap and rinse thoroughly. Remove clothes and remove or scrape fresh foam carefully. If skin irritation continues, consult a doctor. • After eve contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. After swallowing: If symptoms persist consult doctor. Do not induce vomiting; call for medical help immediately. Rinse out mouth and then drink plenty of water. 4.2 Most important symptoms and effects, both acute and delayed Headache Breathing difficulty Coughing Dizziness Allergic reactions 4.3 Indication of any immediate medical attention and special treatment needed Symptomatical treatment (decontamination, vital bodily function) **SECTION 5: Firefighting measures**

# SECTION 5: Fireignung mea

5.1 Extinguishing media
Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray.
For safety reasons unsuitable extinguishing agents: Water with full jet
5.2 Special hazards arising from the substance or mixture Carbon monoxide (CO)
Nitrogen oxides (NOx)
Hydrogen chloride (HCl)
Hydrogen cyanide (HCN)

Can form explosive gas-air mixtures.

(Contd. on page 5)

<sup>—</sup> GB



Replaces: 22.05.2014

Ref: 0045.13.DBR/DL

(Contd. of page 4)

Trade name: SX Hand Held Foam

#### 5.3 Advice for firefighters

· Protective equipment: Wear self-contained respiratory protective device.

### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.
6.2 Environmental precautions:
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for containment and cleaning up:
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Recommended cleaner: acetone
6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
1
SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
Information about fire - and explosion protection:

- Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- **Information about storage in one common storage facility:** Do not store together with oxidizing and acidic materials.
- Further information about storage conditions:
- Keep container tightly sealed.
- Do not seal receptacle gas tight.
- Store in cool, dry conditions in well sealed receptacles.
- Protect from heat and direct sunlight.

(Contd. on page 6)

<sup>-</sup> GB



Replaces: 22.05.2014

Ref: 0045.13.DBR/DL

Trade name: SX Hand Held Foam

(Contd. of page 5)

· 7.3 Specific end use(s) OCF

# **SECTION 8: Exposure controls/personal protection**

• Additional information about design of technical facilities: No further data; see item 7.

#### · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

9016-87-9 diphenylmethanediisocyanate, isomers and homologues

WEL Short-term value: 0.07 mg/m<sup>3</sup> Long-term value: 0.02 mg/m<sup>3</sup> Sen; as -NCO

#### 115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m<sup>3</sup>, 500 ppm Long-term value: 766 mg/m<sup>3</sup>, 400 ppm

• Additional information: The lists valid during the making were used as basis.

#### - 8.2 Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

GB



Replaces: 22.05.2014

Ref: 0045.13.DBR/DL

#### Trade name: SX Hand Held Foam

(Contd. of page 6)

· Eye protection:

69

Tightly sealed goggles

9.1 Information on basic physical a	nd chemical properties	
General Information		
Appearance: Form:	Aerosol	
Form: Colour:	According to product specification	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
<b>Boiling point/Boiling range:</b>	Not applicable, as aerosol.	
Flash point:	< 100 °C	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	235 °C	
Decomposition temperature:	Not determined.	
Self-igniting:	Product is not selfigniting.	
Danger of explosion:	Not determined.	
Explosion limits:		
Lower:	3 Vol %	
Upper:	16 Vol %	
Vapour pressure at 20 °C:	6 bar	
Density at 20 °C:	0.967 g/cm <sup>3</sup>	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not applicable.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wat	er): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	18.5 %	



Replaces: 22.05.2014

Ref: 0045.13.DBR/DL

(Contd. of page 7)

Trade name: SX Hand Held Foam

VOC (EC)

186 g/L18.5 %No further relevant information available.

• 9.2 Other information

# **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No dangerous reactions are known
- 10.2 Chemical stability No decomposition if used according to specifications.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: Acids, bases and oxidants. Amines and alcoholes. Polyols and water
- · 10.6 Hazardous decomposition products:

No dangerous decomposition products known.

Hydrogen cyanide (prussic acid)

Hydrogen chloride (HCl)

Carbon monoxide

Carbon dioxide

Nitrogen oxides

# **SECTION 11: Toxicological information**

· 11.1 Information on toxicological effects

#### • Acute toxicity:

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- Sensitization:
- Sensitization possible through inhalation.
- Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful Irritant

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Carc. 2, Lact.

# **SECTION 12: Ecological information**

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.

(Contd. on page 9)

GB



Replaces: 22.05.2014

Ref: 0045.13.DBR/DL

Trade name: SX Hand Held Foam

(Contd. of page 8)

### · Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

#### **SECTION 13: Disposal considerations**

#### · 13.1 Waste treatment methods

• Recommendation Must not be disposed together with household garbage. Prevent entry into sewers.

· 13.2 Euro	pean waste catalogue	
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS	
08 05 00	wastes not otherwise specified in 08	
08 05 01*	waste isocyanates	
16 00 00	WASTES NOT OTHERWISE SPECIFIED IN THE LIST	
16 05 00	gases in pressure containers and discarded chemicals	
16 05 04*	gases in pressure containers (including halons) containing dangerous substances	
17 00 00	CONSTRUCTION AND DEMOLITION WASTES (INCLUDING EXCAVATED SOIL FROM CONTAMINATED SITES)	
17 06 00	insulation materials and asbestos-containing construction materials	
17 06 04	insulation materials other than those mentioned in 17 06 01 and 17 06 03	

#### · Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number	
ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	1950 AEROSOLS
IMDG	AEROSOLS (alkanes, C14-17, chloro), MARIN
	POLLUTANT
ΙΑΤΑ	AEROSOLS, flammable



Replaces: 22.05.2014

Ref: 0045.13.DBR/DL

### Trade name: SX Hand Held Foam

	(Contd. of pa
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
IMDG	
Class	2.1
Label	2.1
IATA	
*	
Class	2.1
Label	2.1
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
EMS Number:	F-D,S-U
14.7 Transport in bulk according to Anne	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Transport category	2 D
Tunnel restriction code	
UN "Model Regulation":	UN1950, AEROSOLS, 2.1

# **SECTION 15: Regulatory information**

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

(Contd. on page 11)

- GB ·



Replaces: 22.05.2014

Ref: 0045.13.DBR/DL

Trade name: SX Hand Held Foam

(Contd. of page 10)

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# SECTION 16: Other information This information is based on our present knowledge. However, this shall not constitute a guarantee for any

· Relevant phrases

- H220 Extremely flammable gas.
- H280 Contains gas under pressure; may explode if heated.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

specific product features and shall not establish a legally valid contractual relationship.

- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H362 May cause harm to breast-fed children.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

R12 Extremely flammable.

- R12 Extremely hammable.
- R20 Harmful by inhalation.
- R36/37/38 Irritating to eyes, respiratory system and skin.
- R42/43 May cause sensitisation by inhalation and skin contact.
- R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R64 May cause harm to breastfed babies.
- R66 Repeated exposure may cause skin dryness or cracking.

#### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

- IATA: International Air Transport Association
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU) Flam. Gas 1: Flammable gases, Hazard Category 1
- Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
- Press. Gas: Gases under pressure: Compressed gas
- Acute Tox. 4: Acute toxicity, Hazard Category 4
- Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
- Resp. Sens. 1: Sensitisation Respirat., Hazard Category 1
- Skin Sens. 1: Sensitisation Skin, Hazard Category 1
- Carc. 2: Carcinogenicity, Hazard Category 2
- Lact.: Reproductive toxicity, Additional category, Effects on or via lactation STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
- STOT RE 2: Specific target organ toxicity Repeated exposure, Hazard Category 2
- Aquatic Acute 1: Hazardous to the aquatic environment AcuteHazard, Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment Chronic Hazard, Category 1
- Aquatic Chronic 4: Hazardous to the aquatic environment Chronic Hazard, Category 4